



Toroidal Core [MPP, HF, PF, UF, SDT]

Size	Before Finish Dimensions (mm)			After Finish Dimensions (mm)			Path length (cm)	Cross Section Area (cm ²)	AL value (nH/n ²) ±8%							
	OD (±0.3)	ID (±0.3)	HT (±0.3)	OD MAX	ID MIN	HT MAX			26u	50u	60u	75u	90u	125u	147u	160u
038	9.65	4.78	3.18	10.29	4.27	3.81	2.18	0.075	11	21	25	32	38	53	63	68
038A04	9.65	4.78	3.96	10.29	4.27	4.6	2.18	0.094	14	26	32	40	48	66	78	84
040	10.16	5.08	3.96	10.8	4.57	4.6	2.38	0.100	14	26	32	40	48	66	78	84
044	11.18	6.35	3.96	11.89	5.89	4.72	2.69	0.090	11	21	26	32	38	53	63	68
050	12.7	7.62	4.75	13.46	6.99	5.51	3.12	0.114	12	22	27	34	40	56	67	72
065	16.51	10.16	6.35	17.4	9.53	7.11	4.11	0.192	15	29	35	43	52	72	88	92
068	17.27	9.65	6.35	18.03	9.02	7.11	4.14	0.232	19	35	43	53	64	89	105	114
080	20.32	12.7	6.35	21.1	12.07	7.11	5.09	0.226	14	26	32	41	49	68	81	87
090	22.86	13.97	7.62	23.62	13.39	8.38	5.67	0.331	19	35	43	54	65	90	106	115
092	23.6	14.4	8.89	24.3	13.77	9.7	5.88	0.388	22	42	51	63	76	105	124	135
106	26.92	14.73	11.18	27.7	14.1	11.99	6.35	0.654	32	62	75	94	113	157	185	201
106A14	26.92	14.73	14.10	27.7	14.1	15	6.35	0.825	40	78	94	118	142	198	233	253
106A18	26.92	14.73	18.00	27.7	14.1	19	6.35	1.053	51	99	120	151	181	252	297	323
130	33.02	19.94	10.67	33.83	19.3	11.61	8.15	0.672	28	50	61	76	91	127	150	163
130A14	33.02	19.94	14.00	33.83	19.3	15	8.15	0.882	36	65	80	99	119	166	196	213
130A18	33.02	19.94	18.10	33.83	19.3	19	8.15	1.140	47	84	103	128	154	215	254	276
135	34.29	23.37	8.89	35.1	22.56	9.83	8.95	0.454	16	31	38	47	57	79		
141	35.81	22.35	10.46	36.63	21.54	11.28	8.98	0.678	24	47	56	70	84	117		
157	39.88	24.13	14.48	40.72	23.3	15.37	9.84	1.072	35	67	81	101	121	168		
157A18	39.88	24.13	18.00	40.72	23.3	19	9.84	1.332	43	83	100	125	150	208		
157A20	39.88	24.13	20.00	40.72	23.3	21	9.84	1.480	48	92	111	139	167	232		
184	46.74	24.13	18.03	47.63	23.32	18.92	10.74	1.990	59	112	135	169	202	281		
184A15	46.74	28.7	15.24	47.63	27.89	16.13	11.63	1.340	37	70	86	107	128	178		
200	50.8	31.75	13.46	51.69	30.94	14.35	12.73	1.251	32	60	73	91	109	152		
225	57.15	26.39	15.24	58	25.6	16.1	12.5	2.290	60	115	138	172	207	287		
225A14	57.15	35.56	13.97	58	34.7	14.86	14.3	1.444	33	62	75	94	112	156		
244	62	32.6	25.00	63.1	31.37	26.27	14.37	3.675	83	161	192	241	289	402		
292	74.1	49.3	35.00	75.2	44.07	36.27	18.38	5.040	89	171	204	257	309	Tolerance limits		
306	77.8	49.23	12.70	78.9	48.2	13.84	19.6	1.777	30	56	68	85	102	SIZE	Tolerance	
306A16	77.8	49.23	15.88	78.9	48.2	17.02	19.6	2.270	37	71	85	107	128	018 less	±15%	
400	101.6	57.15	13.59	102.87	55.75	14.86	24.27	2.970	40	77	92			025~038	±12%	
400A17	101.6	57.15	16.51	102.87	55.75	17.8	24.27	3.520	47	90	112			040 more	±8%	